



Ejot screw J13-FR 6-5.5 A2

MEZ-SAH-PIN 381/002

vapour barrier Novoproof FA I

MEZ-SAH-PH 381/123

high quality steel
Bl. 4.0 1.4401

steel sheet 3mm galv.

vapour barrier Novoproof FA I

welded slot bolt M8 x 35 8.8
washer Ø8,4 DIN EN ISO 7090 t
hexagon nut M8 DIN EN ISO 40
all components galvanized

variable(89,6)

variable (263,6)

vapour barrier Novoproof FA I

HLTI HST-R M20x200/60

hexagon screw M10x45 DIN EN ISO 4017 8.8
washer Ø10,5 DIN EN 7089-2 8.8
hexagon nut M10 DIN EN 24032 8.8
all components galvanized

steel plate t=10 S355 JR
hot deep galvanized

GRP t=4

MEZ-SAH-PH 381/065

MEZ-SAH-PIN 381/002

steel pipe 60x60x4
S355 J2

Ejot screw J13-FR 6-5.5 A2

GRP t=4

coated with platinum ice

GRP t=4

coated with RAL 7024

silicon joint DC 791 black

walther barrier

Purenit thermo-distance block

steel sheet t=3
S275 ZN

walther barrier

+48.041
ZGRP panel joint level

+47.990
Z-50 from GRP panel joint level

50.8

205.7

+47.785
Ztop of gutter

aluminium sheet t=3 EN AW 5005
powdercoated platinum ice

hexagon screw DIN EN ISO 4017 M10x50 8.8
2x washer DIN EN ISO 7089 M10 8.8
2x hexagon nut DIN EN 24032 M10 8.8

hexagon screw DIN EN ISO 4017 M6x20-A4
+2x washer DIN EN ISO 7089 M6-A4
+2x hexagon nut DIN EN 24032 M6-A4

aluminium U-sheet EN AW 5005
50x60x50x4 anodized

aluminium L-sheet EN AW 5005
78x44x5 anodized

steel pipe 60x60x4
S355 J2

aluminium sheet t=3
EN AW 5005 anodized

GRP t=4

A=0.0781 m²

240

200

306

purenit distance
plate t=5

stainless steel
plate t=6 1.4401

aluminium Z-profil 40x40x40x3
EN AW 5005 anodized

as discussed with our Senior Supervisor
this weep-holes are definitively done on site.

steel U 60x60x5 S355 J2

aluminium U-sheet EN AW 5005 30x74x30x4

stainless steel tube Ø60.3x2,9 1.4401
brush-finished

522.6 (width of Rib)

